


# SLANGEKOBLINGER, STANDARD

## JF – JIC hun 37° konus


Varenummer	Slangestørrelse			JIC gevind størrelse	Dimension (mm)		
	DN	Inch	Dash		F	H	L
0222JF0307	5	3/16"	-3	7/16" - 20	13,5	38,5	14
0222JF0308	5	3/16"	-3	1/2" - 20	15,0	40,0	17
0222JF0407	6,3	1/4"	-4	7/16" - 20	14,0	42,0	14
0222JF0408	6,3	1/4"	-4	1/2" - 20	14,5	42,5	17
0222JF0409	6,3	1/4"	-4	9/16" - 18	16,5	44,5	19
0222JF0508	8	5/16"	-5	1/2" - 20	14,5	42,5	17
0222JF0509	8	5/16"	-5	9/16" - 18	15,5	43,5	19
0222JF0512	8	5/16"	-5	3/4" - 16	17,5	45,5	22
0222JF0609	10	3/8"	-6	9/16" - 18	15,5	46,0	19
0222JF0612	10	3/8"	-6	3/4" - 16	17,5	48,0	22
0222JF0614	10	3/8"	-6	7/8" - 14	18,5	48,0	27
0222JF0812	12,5	1/2"	-8	3/4" - 16	17,5	50,5	22
0222JF0814	12,5	1/2"	-8	7/8" - 14	18,5	51,5	27
0222JF0817	12,5	1/2"	-8	1 1/16" - 12	21,8	54,8	32
0222JF1014	16	5/8"	-10	7/8" - 14	18,7	54,5	27
0222JF1017	16	5/8"	-10	1 1/16" - 12	22,0	57,8	32
0222JF1214	19	3/4"	-12	7/8" - 14	19,5	60,0	27
0222JF1217	19	3/4"	-12	1 1/16" - 12	21,3	61,8	32
0222JF1219	19	3/4"	-12	1 3/16" - 14	25,0	65,5	36
0222JF1221	19	3/4"	-12	1 5/16" - 12	25,5	66,0	41
0222JF1617	25	1"	-16	1 1/16" - 12	22,8	73,8	32
0222JF1621	25	1"	-16	1 5/16" - 12	25,5	76,5	41
0222JF1626	25	1"	-16	1 5/8" - 12	28,5	79,5	50
0222JF2026	31,5	1 1/4"	-20	1 5/8" - 12	27,8	85,5	50
0222JF2030	31,5	1 1/4"	-20	1 7/8" - 12	31,3	89,0	60
0222JF2430	38	1 1/2"	-24	1 7/8" - 12	30,0	94,4	60
0222JF3240	51	2"	-32	2 1/2" - 12	34,0	104,0	75



# SLANGEKOBLINGER, STANDARD

## JF4 – JIC hun 37° konus, 45° bøjning


Varenummer	Slangestørrelse			JIC gevind størrelse	Dimension (mm)			
	DN	Inch	Dash		F	H	L	K
0222JF40307	5	3/16"	-3	7/16" - 20	29,0	54,0	10,0	14
0222JF40308	5	3/16"	-3	1/2" - 20	30,0	55,0	11,0	17
0222JF40407	6,3	1/4"	-4	7/16" - 20	31,0	59,0	10,0	14
0222JF40408	6,3	1/4"	-4	1/2" - 20	32,0	60,0	11,0	17
0222JF40409	6,3	1/4"	-4	9/16" - 18	33,0	61,0	12,0	19
0222JF40508	8	5/16"	-5	1/2" - 20	33,0	61,0	11,0	17
0222JF40509	8	5/16"	-5	9/16" - 18	34,0	62,0	12,0	19
0222JF40512	8	5/16"	-5	3/4" - 16	36,0	64,0	14,0	22
0222JF40609	10	3/8"	-6	9/16" - 18	35,5	66,0	12,0	19
0222JF40612	10	3/8"	-6	3/4" - 16	37,5	68,0	14,0	22
0222JF40614	10	3/8"	-6	7/8" - 14	39,5	70,0	16,0	27
0222JF40812	12,5	1/2"	-8	3/4" - 16	41,0	37,0	14,5	22
0222JF40814	12,5	1/2"	-8	7/8" - 14	43,0	76,0	16,0	27
0222JF40817	12,5	1/2"	-8	1 1/16" - 12	45,5	78,5	19,0	32
0222JF41014	16	5/8"	-10	7/8" - 14	47,0	83,0	16,0	27
0222JF41017	16	5/8"	-10	1 1/16" - 12	50,0	86,0	19,0	32
0222JF41214	19	3/4"	-12	7/8" - 14	64,0	105,0	27,0	27
0222JF41217	19	3/4"	-12	1 1/16" - 12	59,0	99,0	22,0	32
0222JF41219	19	3/4"	-12	1 3/16" - 14	59,0	100,0	22,0	36
0222JF41221	19	3/4"	-12	1 5/16" - 12	61,0	101,0	24,0	41
0222JF41617	25	1"	-16	1 1/16" - 12	83,0	134,0	35,0	32
0222JF41621	25	1"	-16	1 5/16" - 12	72,0	123,0	24,0	41
0222JF41626	25	1"	-16	1 5/8" - 12	76,0	127,0	28,0	50
0222JF42026	31,5	1 1/4"	-20	1 5/8" - 12	95,0	153,0	38,0	50
0222JF42030	31,5	1 1/4"	-20	1 7/8" - 12	88,0	144,0	32,0	60
0222JF42430	38	1 1/2"	-24	1 7/8" - 12	113,0	178,0	46,0	60
0222JF43240	51	2"	-32	2 1/2" - 12	150,0	220,0	61,0	75



# SLANGEKOBLINGER, STANDARD

## JF9 – JIC hun 37° konus, 90° bøjning

Varenummer	Slangestørrelse			JIC gevind størrelse	Dimension (mm)			
	DN	Inch	Dash	F	H	L	K	S
0222JF90307	5	3/16"	-3	7/16" - 20	21,0	46,0	21,0	14
0222JF90407	6,3	1/4"	-4	7/16" - 20	25,5	53,5	26,0	14
0222JF90408	6,3	1/4"	-4	1/2" - 20	25,5	53,5	26,0	17
0222JF90409	6,3	1/4"	-4	9/16" - 18	25,5	53,5	27,0	19
0222JF90508	8	5/16"	-5	1/2" - 20	28,0	56,0	29,0	17
0222JF90509	8	5/16"	-5	9/16" - 18	28,0	56,0	29,0	19
0222JF90609	10	3/8"	-6	9/16" - 18	31,0	61,5	33,0	19
0222JF90612	10	3/8"	-6	3/4" - 16	31,0	61,5	33,0	22
0222JF90812	12,5	1/2"	-8	3/4" - 16	37,0	70,0	39,0	22
0222JF90814	12,5	1/2"	-8	7/8" - 14	37,0	70,0	40,0	27
0222JF91014	16	5/8"	-10	7/8" - 14	45,0	81,0	45,0	27
0222JF91017	16	5/8"	-10	1 1/16" - 12	45,0	81,0	47,0	32
0222JF91214	19	3/4"	-12	7/8" - 14	55,0	95,0	54,0	27
0222JF91217	19	3/4"	-12	1 1/16" - 12	55,0	95,0	53,0	32
0222JF91219	19	3/4"	-12	1 3/16" - 14	55,0	95,0	54,0	36
0222JF91221	19	3/4"	-12	1 5/16" - 12	55,0	95,0	56,0	41
0222JF91617	25	1"	-16	1 1/16" - 12	71,0	122,0	71,0	32
0222JF91621	25	1"	-16	1 5/16" - 12	71,0	122,0	70,0	41
0222JF91626	25	1"	-16	1 5/8" - 12	71,0	122,0	70,0	50
0222JF92026	31,5	1 1/4"	-20	1 5/8" - 12	86,0	143,0	82,0	50
0222JF92030	31,5	1 1/4"	-20	1 7/8" - 12	86,0	143,0	82,0	60
0222JF92430	38	1 1/2"	-24	1 7/8" - 12	102,0	167,0	96,0	60
0222JF93240	51	2"	-32	2 1/2" - 12	137,0	207,0	134,0	75




I udvalgte dimensioner kan JF9 skaffes som 90° short-drop og long-drop.  
Data og dimensioner oplyses på forespørgsel.

# SLANGEKOBLINGER, STANDARD

## JM – JIC han 37° konus

Varenummer	Slangestørrelse			JIC gevind størrelse	Dimension (mm)		
	DN	Inch	Dash	F	H	L	S
0222JM0307	5	3/16"	-3	7/16" - 20	25,0	50,0	12
0222JM0308	5	3/16"	-3	1/2" - 20	25,0	50,0	14
0222JM0407	6,3	1/4"	-4	7/16" - 20	25,5	53,5	12
0222JM0408	6,3	1/4"	-4	1/2" - 20	25,5	53,5	14
0222JM0409	6,3	1/4"	-4	9/16" - 18	26,6	54,6	15
0222JM0508	8	5/16"	-5	1/2" - 20	25,5	53,5	14
0222JM0509	8	5/16"	-5	9/16" - 18	26,6	54,6	15
0222JM0512	8	5/16"	-5	3/4" - 16	29,7	57,7	19
0222JM0609	10	3/8"	-6	9/16" - 18	26,6	57,1	15
0222JM0612	10	3/8"	-6	3/4" - 16	29,7	60,2	19
0222JM0614	10	3/8"	-6	7/8" - 14	34,3	64,8	24
0222JM0812	12,5	1/2"	-8	3/4" - 16	30,7	63,7	19
0222JM0814	12,5	1/2"	-8	7/8" - 14	35,3	68,3	24
0222JM0817	12,5	1/2"	-8	1 1/16" - 12	38,9	71,9	27
0222JM1014	16	5/8"	-10	7/8" - 14	35,5	71,3	24
0222JM1017	16	5/8"	-10	1 1/16" - 12	39,1	74,9	27
0222JM1214	19	3/4"	-12	7/8" - 14	37,3	77,8	27
0222JM1217	19	3/4"	-12	1 1/16" - 12	39,9	80,4	27
0222JM1219	19	3/4"	-12	1 3/16" - 14	41,6	82,1	32
0222JM1221	19	3/4"	-12	1 5/16" - 12	42,1	82,6	34
0222JM1617	25	1"	-16	1 1/16" - 12	41,9	92,9	32
0222JM1621	25	1"	-16	1 5/16" - 12	43,6	94,6	34
0222JM1626	25	1"	-16	1 5/8" - 12	46,8	97,8	42
0222JM2026	31,5	1 1/4"	-20	1 5/8" - 12	47,6	105,3	42
0222JM2030	31,5	1 1/4"	-20	1 7/8" - 12	52,8	110,5	50
0222JM2430	38	1 1/2"	-24	1 7/8" - 12	53,0	117,5	50
0222JM3240	51	2"	-32	2 1/2" - 12	63,4	133,4	65



**SØRENSEN & KOFOED A/S**

SMEDEHOLM 7-9 2730 HERLEV TLF: 44 92 10 88 WWW.SKDK.DK

Dimensioner kan ændres uden forudgående varsel