


PRESSEMÅLSTABEL




SØRENSEN & KOFOED A/S

Sørensen & Kofoed A/S
Smedeholm 7-9
DK-2730 Herlev

Telefon: +45 44 92 10 88
Fax: +45 44 92 22 66
E-mail: sk@skdk.dk
Homepage: www.skdk.dk

SLANGETYPE	MM	20	25	32	40	50
	1/16"	12	16	20	24	32
	TOMMER	3/4"	1"	1. 1/4"	1. 1/2"	2"
 EN 856 4 SP	ICS 400	ICS 412	ICS 416	ICS 420	ICS 424	ICS 432
		35,9	43,0			
		ICS 412	ICS 416	ICS 420	ICS 424	ICS 432
		35,9	42,1	50,6	60,0	73,8
		ICS 412	ICS 416	ICS 420	ICS 424	ICS 432
 EN 856 4 SH		35,8	42,2			
		ICS 412	ICS 416	ICS 420	ICS 424	ICS 432
		35,8	42,1			
		ICS 412	ICS 416	ICS 420	ICS 424	ICS 432
		35,8	42,1			
 EN 856 R 13		35,8	42,1			
		ICS 412	ICS 416	ICS 420	ICS 424	ICS 432
		35,8	42,1			
		ICS 412	ICS 416	ICS 420	ICS 424	ICS 432
		35,8	42,1			
 SAE100 R15		35,8	42,1			
		ICS 412	ICS 416	ICS 420	ICS 424	ICS 432
		35,8	42,1			
		ICS 412	ICS 416	ICS 420	ICS 424	ICS 432
		35,8	42,1			
 EN 856 4 SP	86172201	ICS 512	ICS 516	ICS 620	ICS 624	ICS 632
		32,5	40,4	50,7	59,4	73,6
		41,5	44,5	53	69	78
		ICS 512	ICS 516	ICS 620	ICS 624	ICS 632
		32,7	40,3	46,4	57,4	68,8
 EN 856 4SH		41,5	44,5	52,5	68,5	78
		ICS 512	ICS 516	ICS 620	ICS 624	ICS 632
		33,2	40,8	51,3	60,8	75,7
		41,5	44,5	53	69	78
		ICS 512	ICS 516	ICS 620	ICS 624	ICS 632
 EN 856 R13		33,2	40,8	51,3	60,8	75,7
		41,5	44,5	53	69	78
		ICS 512	ICS 516	ICS 620	ICS 624	ICS 632
		33,2	40,8	51,3	60,8	75,7
		41,5	44,5	53	69	78
 SAE 100 R15		33,2	40,8	51,3	60,8	75,7
		41,5	44,5	53	69	78
		ICS 512	ICS 516	ICS 620	ICS 624	ICS 632
		33,2	40,8	51,3	60,8	75,7
		41,5	44,5	53	69	78

Udv. skrællelængde i mm



ICS
KOBLING

Ovennævnte pressemål er vejledende, koblingens indv. kollapsmål skal være:

Str.:	Min:	Max:
3/4"	12,6	13,3
1"	17,4	18,2
1 1/4"	22,7	23,6
1 1/2"	28,0	29
2"	37,6	38,8