
















PRESSEMÅLSTABEL

SEMPERIT SLANGER





SØRENSEN & KOFOED A/S
 Sørensen & Kofoed A/S
 Smedeholm 7-9
 DK-2730 Herlev
 Telefon: +45 44 92 10 88
 Fax: +45 44 92 22 66
 E-mail: sk@skdk.dk
 Homepage: www.skdk.dk

SLANGETYPE	MM	5	6	8	10	12	16	20	25	32	40	50	
	1/16"	03	04	05	06	08	10	12	16	20	24	32	
	TOMMER	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1. 1/4"	1. 1/2"	2"	
 EN 857 1 SC 02341SC..  SEMPERPAC 1 SNK 02341SNK..	21--		2104	2105	2106	2108	2110	2112	2116				
				14,6	16,2	18,7	21,8	24,3	28,4	36,4			
				2104	2105	2106	2108	2110	2112	2116	2120		
				14,7	16,1	18,6	21,7	24,3	28,4	36,3	46,9		
 EN 857 1SN 0234DIN1SN..  EN 857 2SC 02342SC..  SEMPERPAC 2 SNK 02342SNK..	131--		13104	13105	13106	13108	13110	13112	13116	13120	13124	13132	
				15,4	17,4	19,2	22,6	26,5	30,1	38,2	46,1	53,2	67,6
				13104	13105	13106	13108	13110	13112	13116			
					15,6	17,6	19,5	23,0	27,0	31,1	39,1		
				13104	13105	13106	13108	13110	13112	13116	13120		
				15,8	17,7	19,9	23,2	26,8	30,8	38,7	46,8		
 EN 853 2SN 0234DIN2SN..	232--		23204	23205	23206	23208	23210	23212	23216	23220	23224	23232	
				17	19,1	20,8	24,3	27,8	32,0	40,5	50,5	57,6	70,7

 EN 857 1 SC 02341SC..	 EN 857 1 SN 02342SC..	 EN 857 2 SC 02342SC..	 SEMPERPAC 2 SNK 02342SNK..	132--		13204	13205	13206	13208	13210	13212	13216			
						15,6	17,6	19,3	22,6	25,9	29,8	37,6			
						13204	13205	13206	13208	13210	13212	13216			
						16,1	18,0	20,2	23,2	26,5	30,5	38,5			
						13204	13205	13206	13208	13210	13212	13216			
				16,5	18,2	20,4	23,6	27,0	30,9	39,0					
				13204	13205	13206	13208	13210	13212	13216					
				16,6	18,2	20,4	23,7	27,2	31,2	39,3					
 EN 856 4 SP 02344SP..	 SUPERPAC SPC 3 0234SPC3..	 EN 856 4SH *** 02344SH..	24--				2406	2408	2410	2412	2416	2420	2424	4932	
							22,6	26,3	30	33,3	40,9	50,9	59,8	72,6	
							22	25	27	30	38	45	50	55	
							2406	2408	2410	2412	2416	2420	2424	4932	
							22,0	26,3	29,7	33,8	41,4				
				22	25	27	30	38							
			ICS4--							ICS412	ICS416	ICS420	ICS424	ICS432	
										35,4	42,5	50,7	59,1	73,4	

*** Benyt kun ICS koblinger med ICS hylser

Ovennævnte pressemål er vejledende, koblingens indv. kollapsmål skal være:

 Standard kobling	 Hylser	Flettede slanger			
		Str.:	Min - Max:		
<div style="background-color: #e0e0ff; padding: 5px;">Udv. skrællelængde i mm.</div>		1/4"	3,65 - 3,85		
		5/16"	5,10 - 5,30		
		3/8"	6,30 - 6,50	6,10 - 6,30	
		1/2"	8,60 - 9,00	8,30 - 8,60	
		5/8"	11,20 - 11,70	10,80 - 11,20	
		3/4"	13,60 - 14,10	13,10 - 13,60	12,60 - 13,30
		1"	19,00 - 19,50	18,40 - 19,00	18,30 - 18,60
		1 1/4"	24,90 - 25,40	24,20 - 24,90	23,20 - 23,90
		1 1/2"	30,80 - 31,30	30,00 - 30,80	29,00 - 29,30
		2"	42,50 - 43,00	41,50 - 42,50	39,50 - 40,50