






















PRESSEMÅLSTABEL SEMPERIT SLANGER

SLANGETYPE	MM	5	6	8	10	12	16	20	25	32	40	50	
	1/16"	03	04	05	06	08	10	12	16	20	24	32	
	TOMMER	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1. 1/4"	1. 1/2"	2"	
 EN 857 1 SC 02341SC..  SEMPERPAC 1 SNK 02341SNK..	21--		2104	2105	2106	2108	2110	2112	2116				
			14,6	16,2	18,7	21,8	24,3	28,4	36,4				
				2104	2105	2106	2108	2110	2112	2116	2120		
 EN 857 1SN 0234DIN1SN..  EN 857 2SC 02342SC..  SEMPERPAC 2 SNK 02342SNK..	131--		13104	13105	13106	13108	13110	13112	13116	13120	13124	13132	
			15,4	17,4	19,2	22,6	26,5	30,1	38,2	46,1	53,2	67,6	
				13104	13105	13106	13108	13110	13112	13116			
			15,6	17,6	19,5	23,0	27,0	31,1	39,1				
				13104	13105	13106	13108	13110	13112	13116	13120		
 EN 853 2SN 0234DIN2SN..	232--		23204	23205	23206	23208	23210	23212	23216	23220	23224	23232	
			17,0	19,1	20,8	24,3	27,8	32,0	40,5	50,5	58,0	70,7	

 EN 857 1 SC 02341SC..		132--		13204	13205	13206	13208	13210	13212	13216				
				15,3	17,2	18,8	22,6	25,9	29,5	37,3				
				13204	13205	13206	13208	13210	13212	13216				
				16,1	18,0	20,2	23,2	26,5	30,5	38,5				
				13204	13205	13206	13208	13210	13212	13216				
 EN 857 1 SN 02342SC..				13204	13205	13206	13208	13210	13212	13216				
			16,5	18,2	20,4	23,6	27,0	30,9	39,0					
			13204	13205	13206	13208	13210	13212	13216					
			16,3	18,2	19,5	23,7	26,7	31,2	39,3					
			13204	13205	13206	13208	13210	13212	13216					
 SEMPERPAC 2 SNK 02342SNK..														
 EN 856 4 SP 02344SP..		24--				2406	2408	2410	2412	2416	2420	2424	4932	
							22,6	26,2	30,0	33,3	40,9	50,9	59,8	72,6
							22	25	27	30	38	45	50	55
							2406	2408	2410	2412	2416	2420	2424	4932
							22,0	26,3	29,7	34,0	41,4			
 SUPERPAC SPC 3 0234SPC3..														
 EN 856 4SH *** 02344SH..		ICS4--A							ICS412A	ICS416A	ICS420A	ICS424A	ICS432A	
										36,7	43,0	51,5	59,1	74,8

*** Benyt kun ICS koblinger med ICS hylser

Ovennævnte pressemål er vejledende, koblingens indv. kollapsmål skal være:

Standard kobling	Hylser	Str.:	Flettede slanger	4SP / SPC 3	4 SH (ICS)
			Min - Max:	Min - Max:	Min - Max:
Udv. skrællelængde i mm.		1/4"	3,65 - 3,85		
		5/16"	5,10 - 5,30		
		3/8"	6,30 - 6,50	6,10 - 6,30	
		1/2"	8,60 - 9,00	8,30 - 8,60	
		5/8"	11,20 - 11,70	10,80 - 11,20	
		3/4"	13,60 - 14,10	13,10 - 13,60	12,60 - 13,30
		1"	19,00 - 19,50	18,40 - 19,00	18,30 - 18,60
		1 1/4"	24,90 - 25,40	24,20 - 24,90	23,20 - 23,90
		1 1/2"	30,80 - 31,30	30,00 - 30,80	29,00 - 29,30
		2"	42,50 - 43,00	41,50 - 42,50	39,50 - 40,50