



# KOLLAPSMÅL

Koblingstype	Slangetype	DN mm	5	6	8	10	12	16	19	25	31	38	51
		"	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
		Dash	03	04	05	06	08	10	12	16	20	24	32
Standard	Flettede slanger (f.eks. 1SN / 2SC / 2SN)	Min	2,6	3,6	5,1	6,3	8,6	11,2	13,6	19,0	24,9	30,8	42,0
		Max	2,8	3,8	5,3	6,5	9,0	11,7	14,1	19,5	25,4	31,3	42,5
Standard	Viklede slanger (f.eks. 4SP)	Min		3,4		6,1	8,3	10,8	13,1	18,4	24,2	30,0	41,5
		Max		3,6		6,3	8,5	11,2	13,6	19,0	24,9	30,8	42,5
ICS	Viklede slanger (F.eks. 4SH / R15)	Min							12,6	17,4	22,7	28,0	37,6
		Max							13,3	18,2	23,6	29,0	38,8

Oversigt over kontrolpinde			
Varenummer	Koblingstype	Slange dimension	
0230SCX03-05	Standard	3/16" + 5/16"	
0230SCX04		1/4"	
0230SCX06		3/8"	
0230SCX08		1/2"	
0230SCX10		5/8"	
0230SCX12		3/4"	
0230SCX16		1"	
0230SCX20		1.1/4"	
0230SCX24		1.1/2"	
0230SCX32		2"	
0230SCS1216		ICS	3/4" + 1"
0230SCS2024			1.1/4" + 1.1/2"
0230SCS32			2"



**SØRENSEN & KOFOED A/S**

SMEDEHOLM 7-9 2730 HERLEV TLF: 44 92 10 88 WWW.SKDK.DK