





















PRESSEMÅLSTABEL SEL SLANGER




SØRENSEN & KOFOED A/S

SMEDEHOLM 7-9 2730 HERLEV TLF: 44 92 10 88 WWW.SKDK.DK

SLANGETYPE	MM	5	6	8	10	12	16	20	25	32	40	50	
	1/16"	03	04	05	06	08	10	12	16	20	24	32	
	TOMMER	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1. 1/4"	1. 1/2"	2"	
 EN 853 1SN	13100	13103	13104	13105	13106	13108	13110	13112	13116	13120	13124	13132	
	 EN 857 2SC		15,2	16,1	17,9	20,2	23,7	27,3	31,3	39,6	47,9	54,7	68,3
				13104	13105	13106	13108	13110	13112	13116			
 EN 853 1SN  EN 853 2SN  EN 857 2SC	23200		23204	23205	23206	23208	23210	23212					
			16,7	18,5	20,3	24,0	27,8	31,8					
		23203	23204	23205	23206	23208	23210	23212	23216	23220	23224	23232	
		15,9	18,1	19,9	21,7	25,4	29,3	33,3	42,0	51,7	58,3	72,3	
			23204	23205	23206	23208	23210	23212					
		16,7	18,5	20,2	24,0	27,8	31,9						
 EN 853 1SN	1100									1120	1124	1132	
										45,2	52,7	65,2	
										39	43	58	
 EN 853 1 SN	1200	1203	1204	1205	1206	1208	1210	1212	1216				
		13,0	15,0	16,5	18,5	22,3	26,7	30,8	38,5				
			18	20	20	23	27	27	31	34			

 EN 853 2SN	 EN 857 2SC		1200	1203	1204	1205	1206	1208	1210	1212	1216				
			14,4	16,4	17,9	20,0	23,7	28,2	32,3	40,0					
			18	20	20	23	27	27	31	34					
			1203	1204	1205	1206	1208	1210	1212	1216					
				15,0	16,5	18,4	22,3	26,7	30,7	40,1					
				20	20	23	27	27	31	34					
 EN 853 2SN	2200										2220	2224	2232		
												49,6	57,6	70,5	
											39	43	58		
 EN 853 2 ST	 EN 856 4 SP		2400				2406	2408	2410	2412	2416	2420	2424	4932	
							22,4	25,6	29,2	32,7	41,5	50,6	59,2	71,0	
							22	24	27	30	38	45	50	55	
					2404		2406	2408	2410	2412	2416	2420	2424	2432	
				19,0		23,0	26,7	30,7	34,4	42,0	51,0	60,0	74,0		
				18		22	24	27	30	38	45	50	55		

Ovennævnte pressemål er vejledende, koblingens indv. kollapsmål skal være:



Standard kobling

Hylser

Udv. skrællelængde i mm.

Str.:	Flettede slanger		Viklede 4SP/4SH		Str.:	Flettede slanger		Viklede 4 SP/SH	
	Min.:	Max.:	Min.:	Max.:		Min.:	Max.:	Min.:	Max.:
3/16"	2,6	2,8			3/4"	13,6	14,1	13,1	13,6
1/4"	3,6	3,8	3,4	3,6	1"	19	19,5	18,4	19
5/16"	5,1	5,3			1 1/4"	24,9	25,4	24,2	24,9
3/8"	6,3	6,5	6,1	6,3	1 1/2"	30,8	31,3	30	30,8
1/2"	8,6	9	8,3	8,5	2"	42,5	43	41,5	42,5
5/8"	11,2	11,7	10,8	11,2					

rev. sep 2015