













PRESSEMÅLSTABEL SEL SLANGER




SØRENSEN & KOFOED A/S

SMEDEHOLM 7-9 2730 HERLEV TLF: 44 92 10 88 WWW.SKDK.DK

SLANGETYPE	MM	5	6	8	10	12	16	20	25	32	40	50
	1/16"	03	04	05	06	08	10	12	16	20	24	32
	TOMMER	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1. 1/4"	1. 1/2"	2"
 EN 853 1SN  EN 857 2SC	13100	13103	13104	13105	13106	13108	13110	13112	13116	13120	13124	13132
		15,2	16,1	17,9	20,2	23,7	27,3	31,3	39,6	47,9	54,7	68,3
			13104	13105	13106	13108	13110	13112	13116			
			16,1	17,9	20,1	23,7	27,3	31,4	39,7			
 EN 853 1SN  EN 853 2SN  EN 857 2SC	23200		23204	23205	23206	23208	23210	23212				
			16,7	18,5	20,3	24,0	27,8	31,8				
		23203	23204	23205	23206	23208	23210	23212	23216	23220	23224	23232
		15,9	18,1	19,9	21,7	25,4	29,3	33,3	42,0	51,7	58,3	72,3
			23204	23205	23206	23208	23210	23212				
 EN 853 1SN	1100									1120	1124	1132
										45,2	52,7	65,2
										39	43	58
 EN 853 1 SN	1200	1203	1204	1205	1206	1208	1210	1212	1216			
		13,0	15,0	16,5	18,5	22,3	26,7	30,8	38,5			
		18	20	20	23	27	27	31	34			

 EN 853 2SN	1200	1203	1204	1205	1206	1208	1210	1212	1216			
		14,4	16,4	17,9	20,0	23,7	28,2	32,3	40,0			
		18	20	20	23	27	27	31	34			
		1203	1204	1205	1206	1208	1210	1212	1216			
 EN 857 2SC			15,0	16,5	18,4	22,3	26,7	30,7	40,1			
			20	20	23	27	27	31	34			
 EN 853 2SN	2200									2220	2224	2232
										49,6	57,6	70,5
 EN 853 2 ST	2400				2406	2408	2410	2412	2416	2420	2424	4932
					22,4	25,6	29,2	32,7	41,5	50,6	59,2	71,0
					22	24	27	30	38	45	50	55
			2404		2406	2408	2410	2412	2416	2420	2424	2432
 EN 856 4 SP			19,0		23,0	26,7	30,7	34,4	42,0	51,0	60,0	74,0
			18		22	24	27	30	38	45	50	55
 EN 856 4 SP	4xxA							412A	416A			
	(skrælfri, std kobling)							36,2	43,5			

Ovennævnte pressemål er vejledende, koblingens indv. kollapsmål skal være:



Udv. skrællelængde i mm.

rev. nov 2018

Flettede slanger

Str.:	Min.:	Max.:	Min.:	Max.:
3/16"	2,6	2,8		
1/4"	3,6	3,8	3,4	3,6
5/16"	5,1	5,3		
3/8"	6,3	6,5	6,1	6,3
1/2"	8,6	9	8,3	8,5
5/8"	11,2	11,7	10,8	11,2

Viklede 4SP/4SH

Flettede slanger

Str.:	Min.:	Max.:	Min.:	Max.:
3/4"	13,6	14,1	13,1	13,6
1"	19	19,5	18,4	19
1 1/4"	24,9	25,4	24,2	24,9
1 1/2"	30,8	31,3	30	30,8
2"	42,5	43	41,5	42,5

Viklede 4 SP/SH