

KABEL BESKYTTELSE

1-1C


NYLFLEX PA6 V0

Plastbeskyttelsesslange

Polyamide 6

Polyamide cable conduit

Polyamide 6



Nylflex er en ekstruderet nylonlange i slagfast Nylon (PA6). Slangen er olie- og benzinbestandig, halogenfri samt UV-beständig iht. ISO 8580. UL94-H0 selvslukkende, og anvendt sammen med NH eller SEM forskruingerne sikrer den god beskyttelse af kabler og ledninger. Temperaturområde $\pm 40^{\circ}\text{C}$ / $+120^{\circ}\text{C}$. Standard farver: Grå og sort og andre på forespørgsel.

Nylflex is a corrugated extruded polyamide conduit with excellent mechanical strength. Resistant to acids, mineral oils, benzene etc. and flame retarded. Operating temperature: $\pm 40^{\circ}\text{C}$ / $+120^{\circ}\text{C}$. Our NH adaptors will fit the Nylflex range. Colour: Grey and Black and others on request.

S&K nr.	Dimension indv. x udv. mm.	Længde m/ emballage	Farve	EAN nr.
003102501008	8,4 x 11,7	Rulle 50	Sort	
003102501010	9,9 x 13,0	Rulle 50	Sort	
003102501012	12,2 x 15,7	Rulle 50	Sort	
003102501013	14,2 x 18,5	Rulle 50	Sort	
003102501014	12,7 x 15,8	Rulle 50	Sort	
003102501015	14,2 x 18,5	Rulle 50	Sort	
003102501016	15,0 x 18,9	Rulle 50	Sort	
003102501017	16,6 x 21,2	Rulle 50	Sort	
003102501019	19,3 x 24,3	Rulle 50	Sort	
003102501022	21,3 x 25,4	Rulle 50	Sort	
003102501023	23,2 x 28,3	Rulle 50	Sort	
003102501026	29,0 x 34,5	Rulle 25	Sort	
003102501037	36,0 x 42,4	Rulle 25	Sort	
003102501050	47,7 x 53,7	Rulle 25	Sort	

**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk