

# KABEL BESKYTTELSE

2-3

## MS-PVC-DU BESKYTTELSESSLANGE

Med galvaniseret trådomflet

## MS-PVC-DU FLEXIBLE CONDUIT

With galvanized steel braiding

RoHS

IP 67



Galvaniseret stålslange belagt med brandhæmmende PVC-belægning (Vinnylan) samt flet af galvaniseret jerntråd for ekstra mekanisk styrke. Temperaturtolerance: -25° / +100° C. Til beskyttelse af skarpe spåner og glødende gnister.

*Single – folded galvanic steel conduit covered with non-inflammable PVC-sheath, and reinforced with a galvanized steel braiding for maximum protection. Operating temperature: -25° / +100° C. for Protection against sharp chips and glowing sparks*

S&K nr.	Dimension indv. x udv. mm.	Længde m/ emballage	El nr.	EAN nr.
102316000	7 x 11 mm.	50 m/rulle	8630 271 078	
102317000	10 x 15 mm.	50 m/rulle	8630 271 104	
102318000	13 x 18 mm.	50 m/rulle	8630 271 133	
102319000	15 x 20 mm.	50 m/rulle	8630 271 159	
102320000	17 x 22 mm.	50 m/rulle	8630 271 175	
102321000	21 x 28 mm.	25 m/rulle	8630 271 214	
102322000	28 x 37 mm.	25 m/rulle	8630 271 285	
102323000	37 x 46 mm.	25 m/rulle	8630 271 379	
102324000	44 x 53 mm.	25 m/rulle	8630 271 447	
102325000	48 x 57 mm.	25 m/rulle	8630 271 489	

Forskrninger: Se afsnit 5-4 + 5-5 "RAKKORD".

Bøjningsradius: Ydre diameter x 2 – 2 ½.



**SØRENSEN & KOFOED A/S**

SMEDEHOLM 7-9 2730 HERLEV TLF: 44 92 10 88 WWW.SKDK.DK