

# KABEL BESKYTTELSE

2-4

## ANACONDA SEALTITE® EF

Beskyttelsesslanger

## ANACONDA SEALTITE® EF

Heavy duty conduits



ANACONDA SEALTITE® type EF er en kraftig, men fleksibel beskyttelsesslange for vandtæt ledningsføring (IP67). Temperaturområde:  $\pm 25^{\circ}\text{C}$  /  $+70^{\circ}\text{C}$ . Leveres i grå og sort.

Classification according to NEN-EN-IEC 61386

Compression resistance: Class 4, Heavy (1250N)

Impact resistance: Class 4, Heavy (6J)

Tensile strength: Class 4, Heavy (1000N)

Protection class: IP67

S&K nr.	Type	Dimension indv. x udv. mm	Meter /Krt.	Fittings			El Nr.	Farve
				NPT	ISO	PG		
102244000	EF	3/8" 12,6 x 17,8	75 m	1/2"	M 16	11/13,5	-	Grå
102245000	EF	1/2" 16,0 x 21,1	60 m	1/2"	M 20	16	-	Grå
102246000	EF	3/4" 21,0 x 26,4	50 m	3/4"	M 25	21	-	Grå
102247000	EF	1" 26,5 x 33,1	30 m	1"	M 32	29	-	Grå
102248000	EF	1 1/4" 35,1 x 41,8	30 m	1 1/4"	M 40	36	-	Grå
102450000	EF	2 1/2" 63,3 x 72,6	7,5 m	2 1/2"	M 75	-	-	Grå
102244020	EF	3/8" 12,6 x 17,7	75 m	1/2"	M 16	11/13,5	8630 290 208	Sort
102245020	EF	1/2" 16,0 x 21,1	60 m	1/2"	M 20	16	8630 290 211	Sort
102246020	EF	3/4" 21,0 x 26,4	50 m	3/4"	M 25	21	8630 290 224	Sort
102247020	EF	1" 26,5 x 33,1	30 m	1"	M 32	29	8630 290 237	Sort
102248020	EF	1 1/4" 35,1 x 41,8	30 m	1 1/4"	M 40	36	8630 290 240	Sort
102249020	EF	1 1/2" 40,3 x 47,8	15 m	1 1/2"	M 50	42	8630 290 253	Sort
102250020	EF	2" 51,6 x 59,9	15 m	2"	M 63	48	8630 290 266	Sort

All dimensions without tolerances are for reference only.



**SØRENSEN & KOFOED A/S**

SMEDEHOLM 7-9 2730 HERLEV TLF: 44 92 10 88 WWW.SKDK.DK