

KABEL BESKYTTELSE

2-5

ANACONDA SEALTITE® OR

High temperature. Oil resistance



Robust, extra oil & grease resistant

ANACONDA SEALTITE® type **OR** er modstandygtig overfor olie-produkter, og selv hyppig kontakt med disse produkter påvirker ikke slangens fleksibilitet og funktioner. UV-beständig. Temperaturområde: -15° C - +120° C.

Developed for areas where conduit systems are being exposed to oil and grease. For machine-building industry, diesel-engines, generator-sets, metal, paper, chemical and petrochemical industry.

| S&K nr. | Type | Dimension indv. x udv. mm | Meter/ Krt. | Fittings | | | El nr. | EAN nr. |
|-----------|------|---------------------------------|----------------|----------|-----|---------|--------|---------|
| | | | | NPT | ISO | PG | | |
| 102436000 | OR | 3/8" 12,6x17,8 | 75 | 1/2" | M16 | 11/13,5 | - | |
| 102437000 | OR | 1/2" 16,0x21,1 | 60 | 1/2" | M20 | 16 | - | |
| 102438000 | OR | 3/4" 21,0x26,4 | 50 | 3/4" | M25 | 21 | - | |
| 102439000 | OR | 1" 26,5x33,1 | 30 | 1" | M32 | 29 | - | |
| 102440000 | OR | 1 1/4" 35,1x41,8 | 30 | 1 1/4" | M40 | 36 | - | |
| 102442000 | OR | 2" 51,6x59,9 | 15 | 2" | M63 | 48 | - | |
| 102445000 | OR | 2 1/2" 63,3x72,6 | 15 | 2 1/2" | M75 | - | - | |

Fittings: Siderne 5-4 and 5-7+5-8.

Classification according to NEN-EN-IEC 61386

Compression resistance: Class 4, Heavy (1250N)

Impact resistance: Class 4, Heavy (6 J)

Tensile strength: Class 4, Heavy (1000N)

Protection class: IP 67 (Dust-proof, water-tight)