

KABEL BESKYTTELSE

2-5a

ANACONDA SEALTITE® HCX
Beskyttelsesslanger til høje temperaturer



ANACONDA SEALTITE® type **HCX** er en kraftig beskyttelsesslange som er beregnet for ekstreme temperaturer. UV-bestandigheden gør slangen meget velegnet for udendørs brug. Temperaturområde: -55° C - +160° C.

Conduit with galvanised steel core and TPE cover that is special for extreme high temperature fluctuations. This robust, yet flexible conduit is typically used in transformers, offshore applications, steelworks, foundries and machine building.

S&K nr.	Type	Dimension indv. x udv. mm	Meter/ Krt.	Fittings			El nr.	EAN nr.
				NPT	ISO	PG		
102429000	HCX	3/8" 12,6x17,8	75	1/2"	M16	11/13,5	8630291074	
102430000	HCX	1/2" 16,0x21,1	60	1/2"	M20	16	8630291087	
102431000	HCX	3/4" 21,0x26,4	50	3/4"	M25	21	8630291090	
102432000	HCX	1" 26,5x33,1	30	1"	M32	29	8630291100	
102433000	HCX	1 1/4" 35,1x41,8	30	1 1/4"	M40	36	8630291113	
102434000	HCX	1 1/2" 40,3x47,8	15	1 1/2"	M50	42	8630291126	
102435000	HCX	2" 51,6x59,9	15	2"	M63	48	-	

Fittings: Siderne 5-4 and 5-7+5-8.

Classification according to NEN-EN-IEC 61386

Compression resistance: Class 4, Heavy (1250N)

Impact resistance: Class 4, Heavy (6 J)

Tensile strength: Class 4, Heavy (1000N)

Protection class: IP 67 (dust-proof, water-tight)