

KABEL BESKYTTELSE

2-6

ANACONDA SEALTITE® FGZ

Halogenfri beskyttelsesslanger til fødevarerkontakt



ANACONDA SEALTITE® type **FGZ** er en galvaniseret stålslange med en halogenfri TPE overflade der er beregnet for områder med fødevarerkontakt. FDA godkendt. I dimensionerne 3/8" - 1 1/4" er konstruktionen enkeltfalsat, mens dimensionerne 1 1/2" - 2" er dobbeltfalsat. Temperaturområde: -20° C / +60° C. Produceret iht. EN-61386. Farve: Hvid. FGZ lagerfører pt. ikke.

Sealtite FGZ is a halogen-free conduit specially made for the food industry. The smooth jacket of FDA approved compound is easily cleaned and does not promote bacteria growth. This makes the FGZ perfectly suitable in the food and pharmaceutical industry.

Sealtite FGZ white: Robust, food grade conduit.

S&K nr.	Type	Dimension indv. x udv. mm.	Bøjningsradius (statisk)	Meter/ Krt.	Fittings			EAN nr.
					NPT	ISO	PG	
102471000	FGZ	3/8"	60 mm.	30	1/2"	M16	11/13,5	
102472000	FGZ	12,6x17,8	75 mm.	30	1/2"	M20	16	
102473000	FGZ	1/2"	90 mm.	50	3/4"	M25	21	
102474000	FGZ	16,0x21,1	120 mm.	30	1"	M32	29	
102475000	FGZ	3/4"	135 mm.	15	1	M40	36	
102476000	FGZ	21,0x26,4	165 mm.	15	1/4"	M50	42	
102477000	FGZ	1" 26,5x33,1	210 mm.	15	1	M63	48	
		1 1/4"			1/2"			
		35,1x41,8			2"			
		1 1/2"						
		40,3x47,8						
		2" 51,6x59,9						

Fittings: Se siderne 5-4, 5-6, 5-7+5-8.

Classification according NEN-EN-IEC 61386

Compression resistance: Class 4, Heavy (1250N)

Impact resistance: Class 4, Heavy (6 J)

Tensile strength: Class 4, Heavy (1000N)

Protection class: IP 67 (dust-proof, water-tight)



SØRENSEN & KOFOED A/S

SMEDEHOLM 7-9 2730 HERLEV TLF: 44 92 10 88 WWW.SKDK.DK