

KABEL BESKYTTELSE

3-2

BESKYTTELSESSLANGE I RUSTFRIT STÅL type UI

ANACONDA, dobbeltfalslet rustfri stålslange.

Kerne i rustfrit stål AISI-304



STAINLESS STEEL WIRING CONDUIT ANACONDA

type UI

“fully interlocked” stainless steel strip wound conduit



Type **UI** er en fleksibel dobbeltfalslet beskyttelsesslange uden pakning. Den fuldt dobbeltfalsede konstruktion sikrer ekstrem styrke, fordi profilen hverken kan springe eller snoes op. Typisk anvendelse: Beskyttelse for kabler og kapillarrør og som kraftig beskyttelse i almindelighed.

Yderst modstandsdygtig over for varme. Temperaturområde: -100° C / +600° C.

Materiale: Rustfrit stål AISI 304. AISI 316 kan fremskaffes.

*Type **UI** is a flexible fully interlocked capillary armour tubing without packing. The fully interlocked construction ensures extreme strength, because the profile cannot spring or become unwound.*

Typical applications: protection for wiring and capillary tubing, and as armour. Extreme heat resistant. Temperature range: -100° C / +600° C. Material: stainless steel AISI 304 or AISI 316 (not in stock)

| S&K nr. | Dimension indv. x udv. Mm. | Meter/ karton | Fittings | | | EAN nr. |
|-----------|-------------------------------|------------------|----------|-----|-------|---------|
| | | | NPT | ISO | PG | |
| 102090004 | 4,5 x 7,5 | 100 m. | - | - | - | |
| 102090005 | 5,5 X 8,5 | 100 m. | - | - | - | |
| 102090007 | 8,0 x 11,0 | 100 m. | - | - | - | |
| 102090009 | 9,5 x 12,5 | 30 m. | 5/16" | M16 | PG 9 | |
| 102090013 | 13,0 X 16,0 | 30 m. | 3/8" | M16 | PG 11 | |
| 102090017 | 17,0 X 21,0 | 30 m. | 1/2" | M20 | PG 16 | |
| 102090022 | 22,0 X 26,0 | 30 m. | 3/4" | M25 | PG 21 | |
| 102090025 | 26,0 X 30,0 | 30 m. | 1" | M32 | PG 29 | |
| 102090034 | 34,0 X 39,0 | 30 m. | 1 1/4" | M40 | PG 36 | |
| 102090052 | 52,0 x 58,0 | 15 m. | 2" | - | PG 48 | |

All dimensions without tolerances are for reference only.

Classification according to NEN-EN-IEC 61386

Compression resistance: Class 5, Very Heavy (4000N)

Impact resistance: Class 4, Heavy (6 J)

Tensile strength: Class 4, Heavy (1000N)

Protection class: IP 40.



SØRENSEN & KOFOED A/S

SMEDEHOLM 7-9 2730 HERLEV TLF: 44 92 10 88 WWW.SKDK.DK