

KABEL BESKYTTELSE

5-4D

Forskruning, ISO 90°

Til Anaconda beskyttelsesslanger.

Nickel plated brass fitting, ISO 90°

For Anaconda Sealbite conduits.



Anaconda kompakt montering, UL & SCA, forniklet messing
Konstruktion: Bestående af 4 dele (Forskruning, klemring, tulle og hus)
Temperaturområde: -45°C til + 105°C
Beskyttelsesklasse: IP 67

Anaconda compact fitting, UL & SCA, nickel plated brass
Construction: Consisting of 4 parts (counter nut, clamping ring, ferule and body)
Temperature range: -45°C till +105°C
Protection class: IP 67

S&K nr.	Gevind	Passer til slanger	Antal pr. ks.	EAN nr.
100915016	M16	3/8"	10	
100915020	M20	1/2"	10	
100915025	M25	3/4"	5	
100915032	M32	1"	5	
100915040	M40	1.1/4"	2	
100915050	M50	1.1/2"	2	

Særlige godkendelser: UL-514B og SCA C22.2 (kombineret UL / SCA-fil # 234207)

Egnet til brug i farligt miljø ifølge NEC:

- Artikel 501, stk. 10, litra B) (2) Klasse I, afdeling 2
- Artikel 502, stk. 10, litra A), nr. 2 og B, nr. 2, klasse II, afdeling 1 og 2
- Artikel 503, stk. 10, afsnit A, punkt 3 og B, klasse III, afdeling 1 og 2

Special approvals: UL-514B and SCA C22.2 (combined UL/SCA file # 234207)

Suitable for use in hazardous environment according to NEC:

- Article 501.10 (B) (2) Class I, division 2
- Article 502.10 (A) (2) and (B) (2) Class II, Division 1 and 2
- Article 503.10 (A) (3) and (B) Class III, Division 1 and 2



SØRENSEN & KOFOED A/S

Smedeholm 7-9, 2730 Herlev. Tlf:44921088 www.skdk.dk