

# KABEL BESKYTTELSE

5-4b

## NPT forskruining, lige

Til Sealtite® beskyttelsesslanger.  
Med låseskive

**NPT streight fitting** - For Sealtite® conduits  
Including lock not



## NPT fitting i galvaniseret stål

Til **Sealtite®** beskyttelsesslanger fremstiller ANAMET en serie forskruininger, med Metrisk, PG eller NPT gevind. Messing eller galvaniseret stål. UL/CSA godkendt.

*ANAMET liquid-tight fittings for Sealtite® conduits. Available in PG, NPT or ISO thread. Made out of Brass or galvanized steel. UL/CSA approved.*

### Galvaniseret stål/Galvanized steel

S&K nr.	Gevind/Thread	Passer til slange	El nr.	EAN nr.
100941000	NPT 1/2"	1/2"		
100942000	NPT 3/4"	3/4"		
100943000	NPT 1"	1"		

Thread	Sealtite Size (inch)	Min. Internal Bore (mm)	Dimensions in mm					Standard Package	Weight (Kg/100)
			A	B	C	D	E		
NPT 1/2"	3/8"	10,4	37	15	26	-	24	25	6,8
NPT 1/2"	1/2"	13,7	37	15	29	-	27	25	7,3
NPT 3/4"	3/4"	18,8	38	15	35	-	33	25	10,6
NPT 1"	1"	24,2	44	18	42	-	40	5	15,6
NPT 1.1/4"	1.1/4"	31,6	54	18	56	-	55	5	18,4
NPT 1.1/2"	1.1/2"	36,8	60	18	64	-	61	1	27,0
NPT 2"	2"	48,0	64	18	77	-	77	1	78,0
NPT 2.1/2"	2.1/2"	58,5	86	27	92	-	-	1	154,0
NPT 3"	3"	72,0	94	30	108	-	-	1	206,0
NPT 4"	4"	95,0	102	32	133	-	-	1	298,0



**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk