

# KABEL BESKYTTELSE

5-5

Rustfri forskrning, lige  
Til **U.I./U.I.G** beskyttelsesslanger.

**Stainless steel fitting, straight**  
For **U.I./U.I.G** conduits.



Til **U.I./U.I.G** rustfri beskyttelsesslanger fremstiller Anamet en serie rustfri (AISI 303) forskrninger, med Metrisk, PG eller NPT gevind. Temperaturområde: -45° C / +250° C.

For **U.I./U.I.G** stainless steel conduits Anamet produce AISI 303 fittings, available in PG, NPT or ISO thread. Temperature range: -45° C / +250° C.

S&K nr.	Gevind	Passer til slanger	El nr.	EAN nr.
100810011	PG 11	5/16" slange	-	
100810013	PG 11	3/8" slange	-	
100810016	PG 16	1/2" slange	-	
100810021	PG 21	3/4" slange	-	
100810029	PG 29	1" slange	-	
100810036	PG 36	1 1/4" slange	-	
100810015	M16	3/8" slange	-	
100810020	M20	1/2" slange	-	
100810025	M25	3/4" slange	-	
100810032	M32	1" slange	-	
100810040	M40	1 1/4" slange	-	
100810041	1/2" NPT	3/8" slange	-	
100810042	1/2" NPT	1/2" slange	-	
100810043	3/4" NPT	3/4" slange	-	
100810044	1" NPT	1" slange	-	
100810045	1 1/4" NPT	1 1/4" slange	-	

**At temperature above 105°C the NBR O-ring must be removed.  
A Neoprene seal ring can be an option.**



**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk