

KABEL BESKYTTELSE

5-5C

Rustfri forskruring, lige
Til **Anaconda** beskyttelsesslanger.

Stainless steel fitting, straight
For **Anaconda Sealite** conduits.



Anaconda kompakt montering, UL & SCA, AISI-316 rustfrit stål.

Konstruktion: AISI-316 rustfrit stål bestående af 4 dele (Forskruring, klemring, tulle og hus)

Temperaturområde: -45°C til + 105°C

Beskyttelsesklasse: IP 67

Anaconda compact fitting, UL & SCA, Stainless steel AISI-316.

Construction: Stainless steel AISI-316, consisting of 4 parts (counter nut, clamping ring, ferule and body)

Temperature range: -45°C till +105°C

Protection class: IP 67

S&K nr.	Gevind	Passer til slanger	Antal pr. ks.	EAN nr.
100830016	M16	3/8"	10	
100830020	M20	1/2"	10	
100830025	M25	3/4"	5	
100830032	M32	1"	5	
100830040	M40	1.1/4"	2	
100830050	M50	1.1/2"	2	

Særlige godkendelser: UL-514B og SCA C22.2 (kombineret UL / SCA-fil # 234207)

Egnet til brug i farligt miljø ifølge NEC:

- Artikel 501, stk. 10, litra B) (2) Klasse I, afdeling 2
- Artikel 502, stk. 10, litra A), nr. 2 og B, nr. 2, klasse II, afdeling 1 og 2
- Artikel 503, stk. 10, afsnit A, punkt 3 og B, klasse III, afdeling 1 og 2

Special approvals: UL-514B and SCA C22.2 (combined UL/SCA file # 234207)

Suitable for use in hazardous environment according to NEC:

- Article 501.10 (B) (2) Class I, division 2
- Article 502.10 (A) (2) and (B) (2) Class II, Division 1 and 2
- Article 503.10 (A) (3) and (B) Class III, Division 1 and 2



SØRENSEN & KOFOED A/S

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk