

# KABEL BESKYTTELSE

6-11

## Favorit - kabelforskruning

Metalforskruning med aflastning

## Favorit – Cable gland

Increased anchorage and bending protection



Favorit-forskruningen giver max. sikkerhed ved den store trompet indgang og kraftige trækaflastning. Tæthed og bred anvendelse sikres via løgringen. Gevind iht. DIN 40430. Temperaturområde: -30° C / +100° C. IP55.

*The Favorit-gland means safe cable attachment with the bell shaped entry and the strong traction relief system. Sufficient sealing of several cable diameters is ensured by the multiple sealing rings. PG as per DIN 40430. Temperature range: -30° C / +100° C. IP55.*

S&K nr.	Gevind	Klem-område	Snit i løgringe mm.	EI nr.	EAN nr.
101625000	PG 9	6-8,5 mm.	5x7,5x10	-	
101626000	PG 11	7-11,5 mm.	7,5x10x12	-	
101627000	PG 13,5	8,5-13 mm.	7,5x10x12	-	
101628000	PG 16	9,5-15 mm.	7,5x10x12,5x15	-	
101629000	PG 21	12-19 mm.	10x13x16x19	-	
101630000	PG 29	16,5-27 mm	18x21x24x27	-	

All dimensions without tolerances are for reference only.  
Dimensioner uden toleranceangivelse er kun vejledende.



**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf. 44921088 [www.skdk.dk](http://www.skdk.dk)