

KABEL BESKYTTELSE

6-13

UNIVERSAL VINKEL TYPE F - 90°**UNIVERSAL ELBOW TYPE F - 90°**

Vinkelstykket type F er fremstillet i forniklet trykstøbt zink og forsynet med O-ring. Hermed kan enhver forskruining ændres til en "vinkelforskruing". Op til IP68, afhængig af andre komponenter. Temperaturområde: $\pm 20^{\circ}\text{C}$ / $+100^{\circ}\text{C}$.

The 90° elbow is made of zinc die-cast and fitted with O-ring. Converts any gland into an angle gland. Up to IP68 dependent on the combination with other components. Temperature range: $\pm 20^{\circ}\text{C}$ / $+100^{\circ}\text{C}$.

S&K nr.	Udvendigt gevind	Indvendigt gevind	Gevind/længde	El nr.	EAN nr.
100821000	PG 9	PG 9	6 mm.	8613 129 095	
100822000	PG 11	PG 11	6 mm.	8613 129 118	
100823000	PG 13,5	PG 13,5	6,5 mm.	8613 129 134	
100824000	PG 16	PG 16	6,5 mm.	8613 129 163	
100825000	PG 21	PG 21	6,8 mm.	8613 129 215	
100828000	PG 29	PG 29	8 mm.	8613 129 299	
100829000	PG 36	PG 36	11 mm.	8613 129 367	
100835016	M16	M16	16 mm.	-	
100835020	M20	M20	16 mm.	-	
100835025	M25	M25	16,5 mm.	-	
100835032	M32	M32	18,5 mm.	-	
100835040	M40	M40	19 mm.	-	
100830000	1/2" *	PG 11	7 mm.	8613 129 189	
100831000	1/2" *	PG 13,5	7 mm.	8613 129 202	

**All dimensions without tolerances are for reference only.
Dimensioner uden toleranceangivelse er kun vejledende.**

* Form: Uden krave. * Mould: Without collar

**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk