

# KABEL BESKYTTELSE

6-3en

**EMC-cable gland**  
for cables with shielding  
Metric thread



Nickel plated brass EMC cable glands for cables with shielding. Integrated anchorage, protection against twisting - wide sealing and clamping range. Temperature range -20°C / +100°C. Protection grade IP68 - 5 bar.

Test standard EN 50262 / UL 514B. VDE licence 138870. UL / CSA-File E140310  
SEV licence 02.1466.

Item no.	Thread	Cabledimension total	Thread length	SW	EAN Nr.
101419012	M 12	3-6 mm.	5,0 mm.	14 mm.	
101419116	M 16	5-9 mm.	5,0 mm.	17 mm.	
101419020	M 20	9-13 mm.	6,0 mm.	22 mm.	
101419025	M 25	11-16 mm.	7,0 mm.	27 mm.	
101419032	M 32	14-21 mm.	8,0 mm.	34 mm.	
101419040	M 40	19-27 mm.	8,0 mm.	43 mm.	
101419050	M 50	24-35 mm.	9,0 mm.	55 mm.	
101419063	M 63	32-42 mm.	10,0 mm.	65 mm.	
101419263	M 63	38-48 mm.	10,0 mm.	65 mm.	

### Long Thread:

Item no.	Thread	Cabledimension total	Thread length	SW	EAN No.
101419112	M 12	3-6 mm.	10,0 mm.	14 mm.	
101419216	M 16	5-9 mm.	10,0 mm.	17 mm.	
101419120	M 20	9-13 mm.	10,0 mm.	22 mm.	
101419125	M 25	11-16 mm.	11,0 mm.	27 mm.	
101419132	M 32	14-21 mm.	13,0 mm.	34 mm.	
101419140	M 40	19-27 mm.	13,0 mm.	43 mm.	
101419150	M 50	24-35 mm.	14,0 mm.	55 mm.	
101419163	M 63	32-42 mm.	14,0 mm.	65 mm.	

All dimensions without tolerances are for reference only.



**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk