

KABEL BESKYTTELSE

6-5C

WADI-TEC EMC KABELFORSKRUNING

For EMC beskyttelse i forbindelse med skærmede kabler. **Metrisk** gevind.

WADI-TEC EMC CABLE GLANDS

For EMC protection of shielded cables. Metric thread




Denne EMC forskruring skaber kontinuerlig EMC beskyttelse på grund af tin-belagt klemring. Beskytter mod vrid af kabel. Temperaturområde: $\pm 25^{\circ}\text{C}$ / $+100^{\circ}\text{C}$. Tæthedsgrad IP 68.

Continuous EMC protection due to tin-plated clamping ring. Gas and water-tight (IP 68). Completely twist protected. Temperature range: $\pm 25^{\circ}\text{C}$ / $+100^{\circ}\text{C}$.

Alm. klemområde

| S&K nr. | Gevind | Klemområde | Gevind længde | Nøglevidde | EAN Nr. |
|-------------|--------|---------------|---------------|------------|------------------|
| 66-R1221200 | M 12 | 4,0-6,5 mm. | 7,0 mm. | 14 mm. | 5703 514 419 512 |
| 66-R1221640 | M 16 | 4,0-6,5 mm. | 7,0 mm. | 17 mm. | 5703 514 419 516 |
| 66-R1222040 | M 20 | 7,0-10,5 mm. | 7,0 mm. | 20 mm. | 5703 514 419 520 |
| 66-R1222540 | M 25 | 10,0-14,5 mm. | 8,0 mm. | 24 mm. | 5703 514 419 525 |
| 66-R1223240 | M 32 | 13,5-18,0 mm. | 8,5 mm. | 30 mm. | 5703 514 419 532 |
| 66-R1224040 | M 40 | 14,0-24,0 mm. | 8,5 mm. | 40 mm. | 5703 514 419 540 |

Stort klemområde:



| S&K nr. | Gevind | Klemområde | Gevind længde | Nøglevidde | EAN Nr. |
|-------------|--------|---------------|---------------|------------|------------------|
| 66-R1221600 | M 16 | 5,0-8,5 mm. | 7,0 mm. | 17 mm. | 5703 514 419 514 |
| 66-R1222000 | M 20 | 8,0-12,5 mm. | 7,0 mm. | 22 mm. | 5703 514 419 518 |
| 66-R1222500 | M 25 | 13,5-18,0 mm. | 8,0 mm. | 30 mm. | 5703 514 419 522 |
| 66-R1223200 | M 32 | 17,0-24,0 mm. | 8,5 mm. | 40 mm. | 5703 514 419 527 |
| 66-R1224000 | M 40 | 24,0-30,0 mm. | 8,5 mm. | 50 mm. | 5703 514 419 542 |



SØRENSEN & KOFOED A/S

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk