

# KABEL BESKYTTELSE

6-5b

## MESSING KABELFORSKRUNING

Med langt PG gevind

## NICKEL PLATED BRASS CABLE GLANDS

With long PG thread



Denne messing giver maksimal kabelaflastning pga. klemmelamellerne. Kan også leveres med pakning for reduceret klemmeområde. Temperaturområde:  $\pm 25^{\circ}\text{C}$  /  $+100^{\circ}\text{C}$ . Tæthedegrad: IP68.

Maximum strain relief through clamp lamella. Available with reduction insert. Protection grade: IP 68. Temperature range:  $\pm 25^{\circ}\text{C}$  /  $+100^{\circ}\text{C}$ .

S&K nr.	Gevind	Kabel Klemmeområde	Gevind længde	Nøglevidde	EAN Nr.
101468007-1	PG 7	2,5-6,5 mm.	15 mm.	14 mm.	
101468009-1	PG 9	4,0-9,5 mm.	15 mm.	17 mm.	
101468011-1	PG 11	6,0-11,5 mm.	15 mm.	20 mm.	
101468013-1	PG 13	7,0-13,0 mm.	15 mm.	22 mm.	
101468016-1	PG 16	8,0-15,0 mm.	15 mm.	24 mm.	
101468021-1	PG 21	11,0-19,0 mm.	15 mm.	30 mm.	
101468029-1	PG 29	16,0-26,0 mm.	15 mm.	40 mm.	
101468036-1	PG 36	22,0-34,5 mm.	15 mm.	50 mm.	

### Reduceret klemmeområde:



S&K nr.	Gevind	Kabel Klemmeområde	Gevind længde	Nøglevidde	EAN Nr.
101467307-1	PG 7	1,5-5,0 mm.	15 mm.	14 mm.	
101467309-1	PG 9	2,5-7,0 mm.	15 mm.	17 mm.	
101467311-1	PG 11	3,0-8,5 mm.	15 mm.	20 mm.	
101467313-1	PG 13	4,0-10,0 mm.	15 mm.	22 mm.	
101467316-1	PG 16	5,0-12,0 mm.	15 mm.	24 mm.	
101467321-1	PG 21	8,0-16,0 mm.	15 mm.	30 mm.	
101467329-1	PG 29	11,0-21,0 mm.	15 mm.	40 mm.	
101467336-1	PG 36	16,0-28,0 mm.	15 mm.	50 mm.	

All dimensions without tolerances are for reference only.  
Dimensioner uden toleranceangivelse er kun vejledende.

**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk