

# KABEL BESKYTTELSE

6-9

## PG KABELFORSKRUNING (alm.)

Forniklet messing med standard gummipakning

## PG CABLE GLAND (std.)

Of nickel-plated brass with standard rubber packing ring



PG Kabelforskruning er fremstillet af forniklet messing og leveres med standard eller 3-delt pakning (løgring). DIN 46320. IP 55. Temperaturområde: -30° C / +100° C.

*This cable gland is made of nickel-plated brass and comes with a standard rubber packing ring, alt. multiple sealing. DIN 46320. IP 55. Temperature range: -30° C / +100° C.*

S&K nr.	Dimension	Spænd- område	Gevind/ længde	EI nr.	EAN nr.
101400000	PG 7	5-7 mm.	5 mm.	0913 020 083	
101401000	PG 9	6-8 mm.	6 mm.	0913 020 096	
101403000	PG 11	8-10 mm.	6 mm.	0913 020 106	
101404000	PG 13,5	10-12 mm.	6,5 mm.	0913 020 119	
101406000	PG 16	12-14 mm.	6,5 mm.	0913 020 122	
101408000	PG 21	15-17 mm.	7 mm.	0913 020 135	
101410000	PG 29	24-26 mm.	8 mm.	0913 020 148	
101412000	PG 36	31-33 mm.	9 mm.	0913 020 151	
101414000	PG 42	38-40,5 mm.	10 mm.	0913 020 164	
101415000	PG 48	45-47 mm.	10 mm.	0913 020 177	
101402000	RG 3/8"	8-10 mm..	7 mm.	0913 020 012	
101405000	RG 1/2"	10-12 mm..	7 mm.	0913 020 025	
101407000	RG 3/4"	12-14 mm..	7 mm.	0913 020 038	
101409000	RG 1"	21-23 mm..	7 mm.	0913 020 041	
101411000	RG 1 1/4"	27-29 mm..	7 mm.	0913 020 054	
101413000	RG 1 1/2"	33-35 mm..	7 mm.	0913 020 067	
101416000	RG 2"	45-47 mm..	7 mm.	0913 020 070	

**All dimensions without tolerances are for reference only.  
Dimensioner uden toleranceangivelse er kun vejledende.**



**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk