

# KABEL BESKYTTELSE

7-2R

## KABELFORSKRUNING "PERFECT", Plast

Metrisk. For lille kabeldiameter

## CABLE GLAND "PERFECT", IP 68

Metric. With reduced sealing ring for small cables



Nylon kabelforskruning, vandtæt og montagevenlig. Med reduceret gummipakning for lille kabeldiameter. Tæthed: IP 68. UL/CSA godkendt. Temperaturområde -20° C / +100° C. Farve: Lysegrå RAL 7035. Kan også leveres i sort.

*Polyamide cable gland, watertight and easy-to-assemble. With reduced sealing ring for small cables. Protection grade: IP 68. UL/CSA approved. Temperature range -20° C / +100° C. Colour: Light grey RAL 7035.*

S&K nr.	Gevind	Klem- område	Gevindlængde mm.	El nr.	EAN nr.
101580612	M 12	2-5 mm.	8,0 mm.	-	
101580616	M 16	3-10 mm.	8,0 mm.	-	
101580620	M 20	5-13 mm.	8,0 mm.	-	
101580625	M 25	8-17 mm.	8,0 mm.	-	
101580632	M 32	12-21 mm.	10,0 mm.	-	
101580640	M 40	16-28 mm.	10,0 mm.	-	
101580650	M 50	21-35 mm.	12,0 mm.	-	
99999773/1015 80663	M 63	27-48 mm.	12,0 mm.	-	

All dimensions without tolerances are for reference only.  
Dimensioner uden toleranceangivelse er kun vejledende.



**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk