

KABEL BESKYTTELSE

8-11

KONTRAMØTRIK
Af forniklet messing

LOCK-NUT
Of nickel-plated brass



Sekskantet forniklet messing kontramøtrik. Temperatur op til +200° C.

Hexagonal lock-nut of nickel-plated brass. Temperature range: Up to +200° C.

Metrisk gevind

S&K nr.	Gevind Mx1,5 EN 60423	Højde mm.	Nøglevidde	El nr.	EAN nr.
101150012	M 12	2,8	15 mm.	8613 040 501	
101152016	M 16	2,8	19 mm.	8613 040 514	
101154020	M 20	3,0	24 mm.	8613 040 527	
101156025	M 25	3,5	30 mm.	8613 040 530	
101159032	M 32	4,0	36 mm.	8613 040 543	
101163040	M 40	5,0	46 mm.	8613 040 556	
101166050	M 50	5,0	60 mm.	8613 040 569	
101167063	M 63	6,0	70 mm.	8613 040 572	

PG og RG gevind

S&K nr.	Gevind DIN 40430	Højde mm.	Nøglevidde	El nr.	EAN nr.
101150000	PG 7	2,8	15 mm.	0913 080 081	
101152000	PG 9	2,8	18 mm.	0913 080 094	
101153000	RG 3/8"	3,5	20 mm.	0913 080 010	
101154000	PG 11	3,0	21 mm.	0913 080 104	
101155000	PG 13.5	3,0	23 mm.	0913 080 117	
101156000	RG 1/2"	3,5	24 mm.	0913 080 023	
101157000	PG 16	3,0	26 mm.	0913 080 120	
101158000	RG 3/4"	5,0	30 mm.	0913 080 036	
101159000	PG 21	3,5	32 mm.	0913 080 133	
101160000	RG 1"	4,8	38 mm.	0913 080 049	
101161000	PG 29	4,0	41 mm.	0913 080 146	
101162000	RG 1 1/4"	5,5	48 mm.	0913 080 052	
101163000	PG 36	5,0	51 mm.	0913 080 159	
101164000	PG 1 1/2"	7,0	55 mm.	0913 080 065	
101166000	PG 42	5,0	65 mm.	0913 080 162	
101167000	PG 48	5,0	69 mm.	0913 080 175	
101168000	RG 2"	5,0	66 mm.	0913 080 078	



SØRENSEN & KOFOED A/S

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk