

# KABEL BESKYTTELSE

8-13

## KONTRAMØTRIK

Af **Rustfri stål**

## LOCK-NUT

Of **Stainless steel**

Metrisk sekskantet kontramøtrik af rustfri stål 1.4305 (AISI 303). Metrisk gevind jfr. EN 60423. PG gevind jfr. DIN 40430. Temperatur op til +200° C.

*Metric hexagonal lock-nut of stainless steel 1.4305 (AISI 303). Metric thread as per EN 60423. PG as per DIN 40430. Temperature up to +200° C.*

### Metrisk gevind

S&K nr.	Gevind	Højde mm.	Nøglevidde mm.	El nr.	EAN nr.
101150612	M 12	2,8 mm.	14 mm.	-	
101152616	M 16	2,8 mm.	19 mm.	-	
101154620	M 20	3,0 mm.	24 mm.	-	
101156625	M 25	3,5 mm.	30 mm.	-	
101159632	M 32	4,0 mm.	36 mm.	-	
101163640	M 40	5,0 mm.	46 mm.	-	
101166650	M 50	5,0 mm.	60 mm.	-	
101167663	M 63	6,0 mm.	70 mm.	-	

### PG gevind

S&K nr.	Gevind	Højde mm.	Nøglevidde mm.	El nr.	EAN nr.
101180007	PG 7	3 mm.	14 mm.	-	
101180009	PG 9	3 mm.	19 mm.	-	
101180011	PG 11	3 mm.	22 mm.	-	
101180013	PG 13,5	3 mm.	24 mm.	-	
101180016	PG 16	3 mm.	27 mm.	-	
101180021	PG 21	3,5 mm.	32 mm.	-	
101180029	PG 29	4 mm.	41 mm.	-	
101180036	PG 36	5 mm.	50 mm.	-	

**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk