

# KABEL BESKYTTELSE

8-16

Flerhulspakninger, PG

Sealing Inserts, PG



Pakning ved installation af flere enkelt kabler. Passer til *Perfect* metal- og plastforskruninger. Temperaturområde: – 30° C / +100° C. Materiale: Evopren TPE.

Sealing inserts for installation of several single cables. Temperature range: – 30° C / +100° C. Evoprene TPE.

## PG 9 – PG 13,5

S&K nr.	Gevind størrelse	Dimension $\varnothing \times h$ mm.	Hul opbygning (antal x $\varnothing$ )	EAN Nr.
100909001	PG 9	10,6 x 7,5	2 x 3 mm.	
100909002	PG 9	10,6 x 7,5	2 x 3,5 mm.	
100909003	PG 9	10,6 x 7,5	3 x 2 mm.	
100909004	PG 9	10,6 x 7,5	3 x 3,5 mm.	
100909005	PG 9	10,6 x 7,5	4 x 2 mm.	
100909006	PG 9	10,6 x 7,5	4 x 3 mm.	
100911001	PG 11	13,3 x 8,5 mm.	2 x 3 mm.	
100911002	PG 11	13,3 x 8,5 mm.	2 x 4 mm.	
100911003	PG 11	13,3 x 8,5 mm.	2 x 4,5 mm.	
100911004	PG 11	13,3 x 8,5 mm.	2 x 5 mm.	
100911005	PG 11	13,3 x 8,5 mm.	3 x 3 mm.	
100911006	PG 11	13,3 x 8,5 mm.	3 x 4 mm.	
100911007	PG 11	13,3 x 8,5 mm.	3 x 5 mm.	
100911008	PG 11	13,3 x 8,5 mm.	4 x 3 mm.	
100911009	PG 11	13,3 x 8,5 mm.	7 x 2,7 mm.	
100913001	PG 13,5	15,3 x 8,5 mm.	2 x 4,5 mm.	
100913002	PG 13,5	15,3 x 8,5 mm.	2 x 5 mm.	
100913003	PG 13,5	15,3 x 8,5 mm.	2 x 6 mm.	
100913004	PG 13,5	15,3 x 8,5 mm.	3 x 4 mm.	
100913005	PG 13,5	15,3 x 8,5 mm.	3 x 5 mm.	

All dimensions without tolerances are for reference only.  
Dimensioner uden toleranceangivelse er kun vejledende.



**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk