

KABEL BESKYTTELSE

8-8

PLAST-BLINDPROP

Med krave og kærø

PLASTIC SCREW PLUG



Rund blindpropforskrøning af grå slagfast polystyren (PG) eller nylon (metrisk).
Temperaturområde: -20° C / +70° C (Polystyren) eller -30° C / +100° C (Nylon).

Screw plug of grey polyamide (metric) or polystyrene, (PG). Temperature range: -20° C / +70° C (Polystyrene) or -30° C / +100° C (Polyamide).

Metrisk gevind (Nylon PA6 GF30)

S&K nr.	Gevind M x 1,5	Gevind længde mm.	Hovedbredde mm.	El nr.	EAN nr.
101371012	M 12	6,0	15,0	8613 118 103	
101372016	M 16	6,0	20,0	8613 118 129	
101375020	M 20	6,0	24,0	8613 118 132	
101377025	M 25	8,0	30,0	8613 118 145	
101379032	M 32	8,0	37,0	8613 118 158	
101383040	M 40	8,0	46,0	8613 118 161	
101385050	M 50	10,0	56,0	8613 119 102	
101387063	M 63	12,0	70,0	8613 119 128	

PG og RG gevind (Polystyren)

S&K nr.	Gevind DIN 40430	Gevind længde mm.	Hovedbredde mm.	El nr.	EAN nr.
101371000	PG 7	6	15,0	0913 092 082	
101372000	PG 9	6	19,0	0913 092 095	
101374000	PG 11	6	22,0	0913 092 105	
101375000	PG 13.5	6	25,0	0913 092 118	
101377000	PG 16	6	27,0	0913 092 121	
101379000	PG 21	8	33,0	0913 092 134	
101381000	PG 29	8	44,0	0913 092 147	
101383000	PG 36	10	55,0	0913 092 150	
101385000	PG 42	10	62,0	0913 092 163	
101387000	PG 48	12	69,0	0913 092 176	
101373000	RG 3/8"	9	19,5	0913 092 011	
101376000	RG 1/2"	6	25,0	0913 092 024	

**SØRENSEN & KOFOED A/S**

Smødeholm 7-9, 2730 Herlev. Tlf: 44921088 www.skdk.dk