

KABEL BESKYTTELSE

9-16

Kabelbindere

Polyamid 6.6

Cable ties

Polyamide 6.6



Overholder Mil-S-23190E samt UL94 V2. Bestandig overfor olie, svage syrer og saltvand. Temperatur område: -40° C + 85° C. Selvslukkende og flammehæmmende. Lagerføres i neutral og sort som er UV bestandig. Andre farver efter ønske. **(mindste køb 1 pose a 100 stk.).**

Approval to Mil-S-2390E and UL94 V2. Resistant to oils, salt and diluted acids. Temperature range -40°C / +120°C. Colours black and natural from stock. **(100 pcs. bags).**

S&K nr. Sort	S&K nr. transparent	Længde mm.	Bredde mm.	Diameter mm.	Trækstyrke Kg.	Antal pr. Karton
1210025	1310025	100	2,5	22	8,1	55000
1212025	1312025	120	2,5	25	8,1	45000
1214025	1314025	140	2,5	32	8,1	45000
1216025	1316025	160	2,5	35	8,1	40000
1220025	1320025	200	2,5	50	8,1	30000
1214036	1314036	150	3,6	35	18,0	30000
1220036	1320036	200	3,6	50	18,0	20000
1229236	1329236	292	3,6	77	18,0	17000
1237036	1337036	370	3,6	102	18,0	12000
1212048	1312048	120	4,8	25	22,0	25000
1216048	1316048	160	4,8	38	22,0	16000
1218848	1318848	188	4,8	47	22,0	16000
1220048	1320048	200	4,8	50	22,0	16000
1225048	1325048	280	4,8	60	22,0	12000
1230048	1330048	300	4,8	77	22,0	11000
1236848	1336848	368	4,8	102	22,0	9000
1243048	1343048	430	4,8	110	22,0	7500
1253048	1353048	530	4,8	140	22,0	5500
1229276	1329276	292	7,6	77	54,4	5000
1236876	1336876	368	7,6	102	54,4	4000
1243090	1343090	430	9,0	110	79,4	2500
1253090	1353090	530	9,0	140	79,4	2000
1277590	1377590	775	9,0	228	79,4	1500
1281090	1381090	810	9,0	239	79,4	1500
12103013	13103013	1030	13,0	270	114,0	1000

**SØRENSEN & KOFOED A/S**

Smedeholm 7-9, 2730 Herlev. Tlf. 44921088 www.skdk.dk